



## Technical data Sheet

### ACRYLIC DISTEMPER

#### Description:

Rayband's ACRYLIC DISTEMPER is water based interior wall coating which gives a smooth attractive long lasting matt finish. It is an economical water base wall coating among the Rayband's range of other water based products.

#### Recommended use:

Rayband's ACRYLIC DISTEMPER is an interior coating, which can be applied on all types of plasters, ceiling, asbestos sheets, concrete surfaces etc.

#### Product data:

Covering capacity**	: 12 - 15 sq mtrs/liter /coat
Drying time (surface drying)	: 10 – 15 minutes
Sheen	: Matt
Shades available	: as per Rayband's shade card.
Shelf- life	: 2 years from date of manufacturing In original tightly closed container From direct sunlight and excess Heat.

\*\* Coverage may vary slightly depending on the surface roughness and method of application.

**Recommended Thinner:** Room temperature water

#### Method of application:

Brush or Roller



### **Surface preparation & application:**

Remove the loose particles of previous coatings completely. Sand the surface with fine emery paper and wipe clean. Freshly plastered walls must be allowed to cure completely.

### **Priming:**

Rayband's Interior W/B wall primer (thinned with 15-20% water). Allow the primer to dry for 4 – 5 hours before filling.

### **Filling:**

Apply a thin coat of Rayband's Acrylic wall putty or Smooth Powder putty and sand with fine emery paper. If the surface is uneven, a second thin coat of wall putty can be applied.

### **Finish Coats:**

Apply a thin coat of primer on the putty and allow drying. Then apply 2 coats of Raybands ACRYLIC DISTEMPER thinned with water in the ratio of 2:1 by weight (paint to water) with a recoating interval of 4- 5 hours. A Third coat may be applied to get a better finish.

### **Safety:**

As a general rule avoids contact with eyes. If contact happens clean immediately with water. Clean hands with water and soap solution after painting.