



Technical data sheet

PAINT REMOVER

Description:

Rayband's Paint Remover is formulated to remove and strip old paint film from desired surfaces without damaging the original object. This saves a lot of time and labor as this product gives instant results.

Recommended use:

Rayband's Paint Remover can be used on different surfaces like Steel, aluminium surfaces and wood.

Product data:

Covering capacity** : 8 - 10 sq mtrs/litre

Coverage may vary depending on the surface and method of application

Viscosity @ 30 deg C : Viscous

Sp.Gravity : 1.15 – 1.2

Shelf- life : 3 months date of manufacturing
In original tightly closed container
Away from direct sunlight.

Method of application:

Brush, Roller



Surface preparation & application:

Sprinkle water on the surface from which the old paint film is removed. Give light zig-zag scratches on the paint surface so that the paint remover properly penetrates the paint up to the base. Apply paint remover by brush on the scratched surface.

For better results especially in summer, sprinkle water on the surface where paint remover is applied.

Paint film will immediately start peeling off from the surface. After total peeling of paint film, scrap it and wash it with water properly. If paint layers are more on the surface repeat the method again.

Safety:

Cover Eyes with GLASSES while applying paint remover, In Case of eye contact clean immediately with water and seek medical advice.

Use hand gloves while applying paint remover. Clean hands with water and soap solution after the application. Ensure good ventilation while applying. As it is flammable, take necessary precautions while applying.