



Technical data Sheet

Smooth Acrylic Emulsion

Description:

Rayband's SMOOTH ACRYLIC EMULSION is water based interior wall coating which gives a smooth attractive long lasting matt finish. It is an economic emulsion which is superior to the conventional distempers & gives full value for the money.

Recommended use:

Rayband's SMOOTH ACRYLIC EMULSION is an interior coating which can be applied on all types of plasters, false ceiling, asbestos sheets, concrete etc.

Product data:

Covering capacity** : 20 - 25 sq mtrs/litre
(On normal masonry surface by brushing)

Drying time (surface drying) : 30 minutes
Sheen : Matt
Shades available : as per requirement.
Shelf- life : 3 years from date of manufacturing
In original tightly closed container
Away from direct sunlight and excess heat.

** coverage may vary slightly depending on the surface roughness and method of application.

Recommended thinner: water



Method of application:

Brush , Roller

Surface preparation & application:

Surface preparation: Remove all the loose particles of previous coatings completely. Sand the surface with fine emery paper and wipe clean.

Freshly plastered walls must be allowed to cure completely.

Priming:

Rayband's Interior W/B wall primer (thinned with 15-20% water). Allow the primer to dry for 4 – 5 hours before filling.

Filling:

Apply a thin coat of Rayband's Acrylic wall putty, and sand with fine emery. If the surface is uneven, a second thin coat of wall putty can be applied.

Finish Coats:

Apply a thin coat of primer on the putty and allow drying. Then apply 2 coats of Rayband's SMOOTH ACRYLIC EMULSION thinned with water in the ratio of 2:1 by volume (paint to water) with a recoating interval of 4- 5 hours. A third coat may be applied to get a better finish.

Safety:

As a general rule, avoid contact with eyes. If contact happens, clean immediately with water. Clean hands with water and soap solution after painting.