



## Technical data Sheet

### SMOOTH POWDER PUTTY

#### Description:

Rayband's Smooth powder putty is a Specially formulated putty based on white cement, special binder and effective additives.

#### Recommended use:

To be applied two to three coats on plastered walls as per the condition of the concrete surface.

#### Product data:

Colour	:	White
Viscosity	:	Thick Paste
Covering capacity	:	Depending on surface and thickness
Drying time	:	1-2 hrs

**Recommended thinner:** Water.

#### Surface preparation & Method of application:

1. Before applying "Smooth" Powder Putty the surface should be properly cleaned removing dust, dirt, old paint by a wire brush or putty blade.
2. Wash the wall for cleaning and curing the surface before applying Smooth Powder Putty, so that the dry wall will not



absorb water from the Putty. Preferably apply one coat of Rayband's PWP-2000 on the moist wall which will provides water proofing to the surface and hence will increase life span of applied putty and subsequent paint coat.

3. Mix properly Smooth Powder Putty with 35% to 40% clean water to make the pest as per required consistency.
4. Use the above mixed pest within 90 minutes of its formation, otherwise due to its additive effect will start drying hard.
5. Apply 2 to 3 coats of Smooth Powder Putty on the moist wall with a maximum of 2mm thickness depending on the condition of the wall surface.
6. Coverage of Smooth Powder Putty varies depending on the thickness of putty paste, condition of wall and number of coats.
7. Always store the Smooth Powder Putty in dry place as the product is hygroscopic in nature which may absorb water or moisture from surrounding and get harden.